

PREFERENCES	MENU WRAP	→	DISABLE		
			ENABLE		
	UNITS	→	PREVIOUS MENU		
			METRIC		
			ENGLISH		
				PREVIOUS MENU	
	VEHICLE OPTIONS	TRACTION CTRL			Selectable when vehicle is on
		LOCKING CTRL			
		SAWBAR			
		FAN CTRL			
IDLE OVERRIDE					
			PREVIOUS MENU		
TUNING	INTALL FACTORY				
	INTALL TUNING				
	AXLE RATIO	→	STOCK		
			Common sizes from 2.82 to 5.13		
			PREVIOUS MENU		
	TIRE SIZE	→	STOCK		
			22.50 to 44.00 by .25 Increments		
			PREVIOUS MENU		
	TPMS	→	REAR TIRES	2 PSI to 10 PSI by 1; 10 PSI to 100 PSI by 10	
			FRONT TIRES	2 PSI to 10 PSI by 1; 10 PSI to 100 PSI by 10	
			ALL TIRES	2 PSI to 10 PSI by 1; 10 PSI to 100 PSI by 10	
			PREVIOUS MENU		
	THORTTLE RESP	→	HI (> 40 MPH)	-50% to +50% in 5% Increments	
				PREVIOUS MENU	
			MED (< 40 MPH)	-50% to +50% in 5% Increments	
				PREVIOUS MENU	
			LO (< 10 MPH)	-50% to +50% in 5% Increments	
				PREVIOUS MENU	
	THROTTLE BODY	→	4LO	-50% to +50% in 5% Increments	
				PREVIOUS MENU	
			HYPERTECH	4LO/LO/MID/HI (-50%/0%/20%/20%)	
	IDLE RPM	→	VIPER		
			STOCK		
			PREVIOUS MENU		
		WINCH	→	STOCK	700 RPM to 1800 RPM by 50 RPM Increments 1600 RPM Default
					PREVIOUS MENU
				NORMAL	700 RPM to 1800 RPM by 50 RPM Increments 700 RPM Default
		4LO	→		700 RPM to 1800 RPM by 50 RPM Increments 700 RPM Default
				PREVIOUS MENU	
			4LO	700 RPM to 1800 RPM by 50 RPM Increments 700 RPM Default	
				PREVIOUS MENU	
THERMOSTAT	→	STOCK			
		195			
		180			
		PREVIOUS MENU			
REV LIMIT	→	+/- 500 by 100 RPM Increments			
TOP SPEED	→	STOCK			
			Set per tire ratings, M thru ZR also 25 to 75 by 5 MPH		
		PREMIUM			
ENGINE TUNING	→	REGULAR			
		STOCK			
		PREVIOUS MENU			
DTCS	→	CLEAR (if needed)			
		READ			
		PREVIOUS MENU			
	EXIT				

Start (Key On) →